



Environmental Monitoring Summary Report

Port Kembla Gas Terminal

Infrastructure Approval **SSI-9471**
EPL Licence Number: **21529**

Reporting period: **1 February 2022 – 28 February 2022**

Date published: **11 April 2022**

1 Project background

AIE is responsible for the development of a liquefied natural gas (LNG) import terminal at Port Kembla, south of Wollongong, NSW (the Project). The Project will be the first of its kind in NSW and will provide a simple and flexible solution to the state’s gas supply challenges.

The Project has been declared Critical State Significant Infrastructure (CSSI) in accordance with Section 5.13 of the *Environmental Planning and Assessment Act 1979* (EP&A Act) (NSW) and Schedule 5 of the *State Environmental Planning Policy State and Regional Development* (SRD SEPP). The Project received Infrastructure Approval from the Minister for Planning and Public Spaces on 29 of April 2019.

The construction of the Project is primarily associated with the establishment of a new berth facility at Port Kembla to enable a Liquefied Natural Gas (LNG) Carrier to berth alongside the Floating Storage and Re-gasification Unit (FSRU) and new infrastructure to connect the terminal to the existing gas network. The location of the Project is shown on the Environmental Monitoring Location Plan provided as Appendix A.

An Environment Protection Licence (EPL) (EPL No. 21529) was issued for the Project by the NSW Environment Protection Authority (EPA) on 2 June 2021. The details of the EPL are provided below in Table 1-1.

Table 1-1 EPL Details

EPL No.	21529
Anniversary Date:	2 June
Licensee:	Australian Industrial Energy Pty Ltd
	PO Box 3155 Broadway
	Nedlands WA 6009
Premises:	Port Kembla Gas Terminal, Port Kembla NSW 2505
Scheduled Activity	Contaminated soil treatment
	Crushing, grinding or separating
	Petroleum products storage

2 Report purpose

This Monthly Environmental Monitoring Report has been prepared to provide an overview of project activities undertaken during the reporting period and those forecast for the next reporting period (refer to Section 3) and to satisfy the requirements associated with the publishing of monitoring data and results and reporting requirements required under the relevant conditions of approval and environmental management plans as detailed further in Table 2-1.

Table 2-1 Environmental monitoring reporting requirements

Document	Clause or section	Requirement	Addressed:
DPIE SSI-9471	Sch. 4 Cond. 8	Regular Reporting – The Proponent must provide regular reporting on the environmental performance of the development on its website in accordance with the reporting requirements in any strategies, plans or programs approved under the conditions of this approval.	This report which will be made available on the Project Website.
	Sch. 4 Cond. 12	Access to information – From the commencement of development under this approval, the Proponent shall: (a) Make copies of the following information publicly available on its website:	
		- a comprehensive summary of the monitoring results of the development, reported in accordance with the specifications in any conditions of this approval, or any approved plans and programs	Section 4
		- a summary of complaints, which is to be updated monthly	Section 5
AIE Air Quality Management Plan (Stage 2A)	Section 11.4	A monthly environmental monitoring report will be developed for each calendar month which will include details of the monitoring results and frequencies and inclusion of any exceedance of EPL No. 21529 air monitoring limits / criteria. A copy of the monthly environmental monitoring report will be made available on the AIE Project website.	Air quality monitoring results and frequencies and inclusion of any exceedance provided in Section 4.1
AIE Water Quality Management Plan (Stage 2A)	Section 9.4	A monthly environmental monitoring report will be developed for each calendar month which will include details of the monitoring results and frequencies and inclusion of any exceedance of EPL (No. 21529) water quality monitoring limits / criteria. A copy of the monthly environmental monitoring report will be made available on the AIE Project website.	Water quality monitoring results and frequencies and inclusion of any exceedance provided in Section 4.2
EPL 21529	Condition M6.2	The licensee must monitor and record temperature, humidity, wind direction, wind velocity and rainfall at either the project weather station, or through analysis of equivalent weather information obtained from the Australian Bureau of Meteorology. Whilst there are no specific requirements to provide weather data in the monthly report, AIE has included the data for transparency and to assist with context for any monitoring results where required.	Section 6



3 Project activities

3.1 Project status

The project has progressed to Stage 2A: Marine Berth Construction – Land Based. The Stage 2A works include:

- Quay wall construction
- Installation of communications conduit, potable water line, and 11kV power cable and Pad-mount Substation within the Marine Berth Construction and Dredging (MBD) Site Compound
- Construction of the Onshore Receiving Facilities (ORF), which comprises three areas: Wharf Topside Area; Utility Area; and Common Area
- Pipeline construction and associated ancillary infrastructure within MBD Site Compound delivered as part of ORF scope

3.2 Project activities for the reporting month

- Completion of piling pad
- Installation of wharf king piles
- Installation of rear sheet pile wall

3.3 Project activities for the upcoming month

- Ongoing installation of wharf king piles
- Ongoing installation of rear sheet pile wall

4 Environmental monitoring data

The following sections present a summary of the air quality, water quality and weather monitoring data for the reporting month.

A copy of this report will be made available on the Project website at the following web-address:

<https://ausindenergy.com/environmental-information/>

4.1 Air quality

4.1.1 Air Quality Monitoring Locations and Frequency

Air quality monitoring equipment is installed to the north and south of the MBD site compound (Berth 101), and to the east and west and central portion of the Outer Harbour stockpile area.

A summary of the air quality monitoring locations are provided below in Table 4-1 and a monitoring location plan is provided in Appendix A.

Table 4-1 Air quality monitoring locations

EPL Ref.	Monitoring location	Monitoring type	Monitoring parameter	Monitoring frequency
8	Northern boundary of the premises, adjacent the southern boundary of Port Kembla Coal Terminal	Dust Deposition Gauge and Ambient Air Monitoring - High Volume Air Sampler	Particulates - Deposited Matter (gm/m ² /month) and Total suspended particles (TSP) (ug/m ³)	Monthly
10	Southern boundary of Berth 101			
12	Southern side of emplacement area, Outer Harbour			
14	Eastern side of emplacement area, Outer Harbour			Special Frequency 1 (24-hour period every 6 days)
22	Northern side of emplacement area, Outer Harbour			
9	Northern boundary of the premises, adjacent the southern boundary of Port Kembla Coal Terminal	Real time dust monitoring	PM10 (ug/m ³)	Continuous
11	Southern boundary of Berth 101			
13	Southern side of emplacement area, Outer Harbour			
15	Eastern side of emplacement area, Outer Harbour			
23	Northern side of emplacement area, Outer Harbour			

4.1.2 Air Quality Monitoring Results

The air quality monitoring results for the reporting month are presented below in Table 4-2.

Table 4-2 Air quality monitoring results

Monitoring Location (EPL Reference)		Monitoring parameter						Events above criteria ¹	
		Particulates Deposited Matter (Depositional dust gauge) ²	Total Suspended Particles (High Volume Air Sampler)			PM10 (Real-time tracker)			
			Average	Minimum	Maximum	Average	Minimum		Maximum
Unit		g/m ² /month	mg/m ³	mg/m ³	mg/m ³	ug/m ³ /24 hours	ug/m ³ /24 hours	ug/m ³ /24 hours	No.
Criteria		NA	NA	NA	NA	NA	NA	200	NA
Berth 101 North	EPL 8	5.60	0.19	0.06	0.48	No PM10 monitoring required at this EPL Point			NA
	EPL 9	No Dust Deposition Gauge or HiVol required at this EPL Point				58.99	23.40	352.67	1
Berth 101 South	EPL 10	3.70	0.17	0.05	0.00	No PM10 monitoring required at this EPL Point			NA
	EPL 11	No dust gauge or HiVol required at this EPL Point				42.85	16.08	119.46	0
Outer Harbour South	EPL 12	0.50	0.04	0.01	0.00	No PM10 monitoring required at this EPL Point			NA
	EPL 13	No dust gauge or HiVol required at this EPL Point				15.04	5.03	28.79	0
Outer Harbour East	EPL 14	0.20	0.06	0.03	0.00	No PM10 monitoring required at this EPL Point			NA
	EPL 15	No dust gauge or HiVol required at this EPL Point				18.38	5.02	29.83	0
Outer Harbour North	EPL 22	1.20	0.05	0.04	0.00	No PM10 monitoring required at this EPL Point			NA
	EPL 23	No dust gauge or HiVol required at this EPL Point				20.65	5.47	46.77	0

¹Includes individual number of times results recorded above criteria (200ug/m³/24 hours). Refer to Appendix B for event above criteria reports.

²Assessed as Total Insoluble.

4.2 Water quality

4.2.1 Water Quality Monitoring Locations and Frequency

Water quality monitoring is undertaken at five (5) locations within the Port Kembla harbour. Each water quality monitoring location is securely anchored/moored in its location. Details of each of the water quality monitoring locations and corresponding EPL license reference is provided below in Table 4-3.

Table 4-3 Harbour water quality monitoring locations

EPL Ref.	Monitoring location	Type of monitoring	Parameters	
			Continuous monitoring at 15 min intervals	Weekly grab sample
1	WQM1 - North of Berth 101	Primary- impact works area receiver	- Turbidity - Temperature - pH - Salinity (EC) - Dissolved oxygen	- Aluminium
16	WQM2 - North of the emplacement cell, Outer Harbour.	Primary- impact works area receiver		- Anthracene
17	WQM3 - South West of Berth 101	Primary- impact works area receiver		- Arsenic
18	WQM4 - Near the Pacific Ocean entrance to Outer Harbour	Background water quality		- Benzo(a)pyrene
19	WQM5 - Near entrance to Allans Creek, near Bluescope Steel	Background water quality		- Cadmium
				- Chromium (total)
				- Cobalt
				- Copper
				- Lead
				- Mercury
				- Naphthalene
				- Nickel
				- Total PAHs
				- TSS
				- Tributyltin
				- Zinc

In addition to the monitoring requirements listed above for the harbour, monitoring is also required for any discharge event from the on-site sedimentation basin located at the southern end of Berth 101. Details of the monitoring requirements associated with the sediment basin discharge point are included below in Table 4-4.

Table 4-4 Sediment basin discharge monitoring

EPL Ref.	Monitoring location	Type of monitoring	Parameters	
			Prior to discharge	Daily grab sample during discharge
20	Sediment basin discharge point at the southern end of Berth 101	Wet weather discharge quality	- Oil and grease (visual) - Total suspended solids (TSS)	- Aluminium - Arsenic - Cadmium - Chromium - Cobalt - Copper - Lead - Mercury - Nickel - Oil and grease (visual) - pH - Total PAHs - Tributyltin - TSS - Zinc

4.2.2 Continuous Water Quality Monitoring Results

A summary of the results for the continuous water quality monitoring in the harbour is presented below in Table 4-5. Further details for exceedances as indicated below are provided in Appendix B.

Table 4-5 Harbour water quality – Continuous monitoring results

Monitoring location	Statistic	Results - based on individual 15-minute median				
		Turbidity (NTU)	Temperature (Deg. C)	pH	Electrical conductivity (uS/cm)	Dissolved Oxygen (%sat)
Criteria		25 (NTU) / 50 (TSS) ¹	N/A	N/A	N/A	N/A
WQM1 / EPL 1	Average	4.0	23.5	8.2	49317.1	90.3
	Minimum	1.2	19.7	6.5	26640.7	67.2
	Maximum	123.0	27.1	8.3	52969.4	115.6
	Events above criteria ²	0	-	-	-	-
WQM2 / EPL 16	Average	2.5	23.4	8.2	51108.8	97.1
	Minimum	1.3	19.2	8.1	36441.9	80.1
	Maximum	75.3	25.7	8.3	52928.6	118.9
	Events above criteria ²	0	-	-	-	-
WQM3 / EPL 17	Average	3.8	23.7	8.2	49613.0	94.6
	Minimum	1.0	20.2	7.9	21349.9	79.4
	Maximum	63.1	28.0	8.3	53114.2	118.1
	Events above criteria ²	0	-	-	-	-
WQM4 / EPL 18 (Background)	Average	2.8	23.4	8.2	51063.4	95.5
	Minimum	1.2	20.0	8.1	27776.7	80.3
	Maximum	58.7	26.4	8.3	53326.1	118.3
WQM5 / EPL 19 (Background)	Average	12.0	25.9	8.3	47720.8	95.1
	Minimum	1.3	19.8	7.7	15607.8	71.8
	Maximum	423.6	33.0	8.9	52819.9	115.2

¹Indicative value based on previous EPL's issued at Port Kembla indicate that 50 mg/l of suspended sediment is equal to 25 NTU (as per CWQMP)

²Includes individual number of times results exceeded background. Refer to Appendix B for exceedance reports.



4.2.3 Water Quality Monitoring Results – Port Kembla Harbour Grab Samples

A summary of the results for the Port Kembla Harbour weekly grab samples is presented below in **Error! Not a valid bookmark self-reference.** Further details for exceedances as indicated below are provided in Appendix B.

Table 4-6 Harbour water quality – Weekly grab sample results summary

Monitoring Location	Statistic	Aluminium	Anthracene	Arsenic	Benzo(a)pyrene	Cadmium	Chromium (total)	Cobalt	Copper ³	Lead	Mercury	Naphthalene	Nickel ³	Total PAHs	Total Suspended Solids (TSS)	Tributyltin	Zinc
Unit		ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	Ug/L	ug/L	ug/L	ug/L	mg/L	ngSn/L	ug/L
Criteria ²		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	50 + BG	N/A	N/A
WQM1/ EPL 1	Average	<5	<0.1	1.75	<0.05	<1	<0.5	<1	1.25	<0.2	<0.1	<0.1	0.58	<0.05	<5	<2	<5
	Minimum	<5	<0.1	1.60	<0.05	<1	<0.5	<1	1.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Maximum	<5	<0.1	1.90	<0.05	<1	<0.5	<1	2.00	<0.2	<0.1	<0.1	0.80	<0.05	<5	<2	<5
	Events above criteria ¹	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
WQM2/ EPL16	Average	<5	<0.1	1.73	<0.05	<1	<0.5	<1	1.25	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Minimum	<5	<0.1	1.60	<0.05	<1	<0.5	<1	1.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Maximum	<5	<0.1	1.80	<0.05	<1	<0.5	<1	2.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Events above criteria ¹	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
WQM3/ EPL17	Average	<5	<0.1	1.73	<0.05	<1	<0.5	<1	1.25	<0.2	<0.1	<0.1	0.55	<0.05	<5	<2	<5
	Minimum	<5	<0.1	1.60	<0.05	<1	<0.5	<1	1.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Maximum	<5	<0.1	1.80	<0.05	<1	<0.5	<1	2.00	<0.2	<0.1	<0.1	0.70	<0.05	<5	<2	<5
	Events above criteria ¹	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
WQM4/ EPL18	Average	<5	<0.1	1.70	<0.05	<1	<0.5	<1	1.25	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Minimum	<5	<0.1	1.70	<0.05	<1	<0.5	<1	1.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Maximum	<5	<0.1	1.70	<0.05	<1	<0.5	<1	2.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
WQM5/ EPL19	Average	<5	<0.1	1.80	<0.05	<1	<0.5	<1	1.50	<0.2	<0.1	<0.1	0.78	<0.05	<5	<2	<5
	Minimum	<5	<0.1	1.50	<0.05	<1	<0.5	<1	1.00	<0.2	<0.1	<0.1	0.50	<0.05	<5	<2	<5
	Maximum	<5	<0.1	2.10	<0.05	<1	<0.5	<1	2.00	<0.2	<0.1	<0.1	1.50	<0.05	<5	<2	<5

¹Includes individual number of times results exceeded background. Refer to Appendix B for exceedance reports.

²BG = Background (WQM4 / WQM5)

³In place of a non-detect, the Limit of Reporting (LOR) for this analyte and method has been substituted to calculate the above statistics.



4.2.4 Water Quality Monitoring Results – Sediment basin discharge

During the reporting month, there were seventeen (17) authorised discharge events and three (3) discharge events as a result of excessive rainfall exceeding the design criteria of the basin (>43.5 mm in any 5-day period). Refer to Section 4.3 for site weather monitoring details. The date of the events and a summary of the water quality results for the authorised discharge events from the sediment basin is included below in Table 4-8.

Table 4-7 Sediment basin discharge water quality – Pre-discharge and daily grab sample results

Date of discharge/ sampling	Aluminium	Arsenic	Cadmium	Chromium	Cobalt	Copper	Lead	Mercury	Nickel	Zinc	Tributyltin	TSS	pH	Oil & Grease	Total PAH	Overflow Discharge?	Rainfall (mm) Roll. 5-day total
	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	mg/L	-	-	µg/L	-	mm
Criteria	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	50	NA	Visible	NA	NA	NA
03/02/2022	6	0.5	<0.05	0.3	0.1	1.2	<0.1	<0.1	1.3	4	<2	5	7.55	<5	<0.05	N	-
07/02/2022	<5	0.5	<0.05	3.1	0.1	1.0	<0.1	<0.1	<0.5	1	<2	<5	6.97	<5	<0.05	N	-
08/02/2022	8	0.5	<0.05	2.9	0.1	2.8	<0.1	<0.1	<0.5	<1	<2	<5	7.16	<5	<0.05	N	-
09/02/2022	<5	0.4	<0.05	2.9	0.1	1.1	<0.1	<0.1	<0.5	<1	<2	<5	6.72	<5	<0.05	N	-
10/02/2022	11	0.5	<0.05	3.0	<0.1	2.5	<0.1	<0.1	1.6	2	<2	<5	6.73	<5	<0.05	N	-
11/02/2022	105	1.7	<0.05	3.0	<0.1	1.1	<0.1	<0.1	<0.5	<1	<2	<5	6.95	<5	<0.05	N	-
14/02/2022	14	0.6	<0.05	2.9	<0.1	1.0	<0.1	<0.1	<0.5	1	<2	<5	8.60	<5	<0.05	N	-
15/02/2022	18	0.6	<0.05	2.8	<0.1	2.7	<0.1	<0.1	0.5	4	<2	<5	7.03	<5	<0.05	N	-
16/02/2022	32	0.6	<0.05	2.9	<0.1	1.6	<0.1	<0.1	<0.5	2	<2	<5	6.44	<5	<0.05	N	-
18/02/2022	8	0.5	<0.05	2.8	<0.1	1.3	<0.1	<0.1	<0.5	<1	<2	<5	6.73	<5	<0.05	N	-
21/02/2022	7	0.5	<0.05	2.5	<0.1	2.2	<0.1	<0.1	<0.5	<1	<2	<5	7.41	<5	<0.05	N	-
22/02/2022	5	<0.5	<0.2	2.7	<0.2	2	<0.2	<0.1	<0.5	<5	<2	<5	7.10	<5	<0.05	N	-
23/02/2022	14	0.6	<0.05	2.3	<0.1	1.0	<0.1	<0.1	<0.5	<1	<2	<5	7.30	<5	<0.05	N	-
24/02/2022	24	0.5	<0.05	2.5	<0.1	1.3	<0.1	<0.1	<0.5	<1	<2	<5	6.70	<5	<0.05	N	-
25/02/2022	546	1.3	<0.05	2.6	<0.1	1.3	<0.1	<0.1	<0.5	<1	<2	<5	7.19	<5	<0.05	Y	170.2
26/02/2022	1510	1.4	<0.05	3.4	<0.1	1.5	<0.1	<0.1	<0.5	<1	<2	<5	7.54	<5	<0.05	Y	208.4
28/02/2022	848	1.0	<0.05	3.2	<0.1	1.1	<0.1	<0.1	<0.5	<1	<2	<5	7.95	<5	<0.05	Y	154.6



4.3 Weather station results

Under the EPL (Condition M6.2), AIE is required to monitor and record temperature, humidity, wind direction, wind velocity and rainfall at either a project weather station, or through analysis of equivalent weather information obtained from the Australian Bureau of Meteorology.

AIE established and maintains a weather station for the project site located at the southern point of Berth 101 (EPL monitoring point 21) as shown in Figure of Appendix A. The data obtained from the onsite weather station for the reporting period is provided below in Table 4-8.

Table 4-8 Site weather station monitoring results summary

Parameter	Unit of measure	Monthly statistic	Result EPL Point 21
Wind velocity	m/s (15min average)	Average	4.58
		Maximum	0.13
		Minimum	11.73
Wind direction at 10m	Degrees (1hr average)	Average	21.81
Rainfall rate	mm/hr (1hr average)	Average	0.57
		Maximum	0.00
		Minimum	17.20
Rainfall (Total)	mm	Monthly total	386.60
Temperature	Degrees Celsius	Average	21.81
		Maximum	14.80
		Minimum	29.00
Humidity	%	Average	80.19
		Maximum	42.50
		Minimum	100.00



5 Environmental complaints

A summary of environmental complaints received during the reporting month and follow-up close-out and or corrective actions are presented below in Table 5-1.

Table 5-1 Environmental complaints summary

Date	Complaint No.	Nature of the complaint	Follow-up close-out and or corrective action
NA	NA	No environmental complaints received for the reporting month	NA



Appendices

Appendix A - Monitoring location plan



<p>Paper Size: ISO A4 0 0.1 0.2 0.3 0.4 Kilometers</p>			<p>Australian Industrial Energy Port Kembla Gas Terminal</p>	<p>Project No. 21-27477 Revision No. - Date 04/06/2021</p>
<p>Map Projection: Transverse Mercator Horizontal Datum: GDA 1994 Grid: GDA 1994 MGA Zone 56</p>			<p>EPL Licence Premises Stage 1</p>	<p>FIGURE 1</p>

Data source: Aerial imagery - nearmap 2021 (image date 16/04/2018, date extracted 18/02/2019); General topo - NSW LPI DTDB 2017 & 2015; Cadastre - NSW LPI DCDB 2017. Created by: aldrich

Appendix B – Summary of Events Above Criteria

Each exceedance triggers an investigation including the evaluation of wind direction, comparison of upwind and downwind monitors at the time of the event. Dust prevention controls are continually being assessed to ensure their adequacy.

Air Monitoring Events Above Criteria

Date	Location	Exceedance value (ug/m ³ /24 hours)	Investigation & Actions
03/02/2022	EPL 9	352.65	High winds elevated dust levels across Port Kembla. Water cart in operation. Monitoring indicated results above the first and second trigger action levels (200 ug/m ³ peak) but below the performance criteria (90 ug/m ³ as an annual rolling average).

Water Monitoring Events Above Criteria

Date	Location	Recorded Value	Action Taken	Investigation Outcomes
No events above criteria in reporting period				